


SPW / SB-SOBWN Oilless Thrust Washer 止推垫片



Material Specifications 材料
材料: 高力青铜+固体润滑剂
CuZn25Al5Mn4Fe3 + Graphite(500#SP)

Housing Tolerance 相配座孔公差
相配座孔公差等级推荐H7
Housing tolerance recommended H7

How To Order 订单方式

Code	d	T
● SPW	09 03	
● SOBWN	08 03	

Unit(单位): mm

SinoBronze Standard No.	I.D. φd 内径	O.D. φD 外径	T Thickness 厚度	Screw Holes 螺丝孔							
				P.C.D	Number of Holes 数量	Flat Head Screw 规格	d1				
● SPW-0603 SOBW-0603	6.2	25	3	15	2	M3	3.5				
● SPW-0803 SOBW-0803	8.2	28		18							
SPW-1003 SOBW-1003	10.2	30		20							
SPW-1203 SOBW-1203	12.2	40		28							
SOBWN-1203				Without flat head screw hole 无平头螺丝孔							
SPW-1303 SOBW-1303	13.2	50		5	28	2	M3	3.5			
SPW-1403 SOBW-1403	14.2				35						
SPW-1503 SOBW-1503	15.2				Without flat head screw hole 无平头螺丝孔						
SPW-1603 SOBW-1603	16.2										
SOBWN-1603											
SPW-1803 SOBW-1803	18.2					35	M3	3.5			
SPW-2005 SOBW-2005	20.2				7	7	40	2	M5	6	
SPW-2505 SOBW-2505	25.2		55								
SPW-3005 SOBW-3005	30.2		60								
SPW-3505 SOBW-3505	35.2		70								
SPW-4007 SOBW-4007	40.2		8				8	60	2	M6	7
SPW-4507 SOBW-4507	45.2							67.5			
SPW-5008 SOBW-5008	50.3	75									
SPW-5508 SOBW-5508	55.3	85									
SPW-6008 SOBW-6008	60.3	90		4				M8	9		
SPW-6508 SOBW-6508	65.3	125									
SPW-7010 SOBW-7010	70.3	130									
SPW-7510 SOBW-7510	75.3	140									
SPW-8010 SOBW-8010	80.3	10		10	120	4		M10	11		
SPW-9010 SOBW-9010	90.5				170						
SPW-10010 SOBW-10010	100.5				190						
SPW-12010 SOBW-12010	120.5				200						