


Spring Bushings with Arrow-Shaped Slot

(Produced on Request)



d	D	D1	外径 O.D.	内径 I.D.	座孔 Housing Bore (H8)	轴 Shaft (f8)	f ₁	f ₂	L 0.50											
									10	15	20	25	30	40	50	60	80	90	100	
14	20	20	+0.052	14	+0.033	14	-0.016	2.2	1	●	●	●	●							
15	20	20	+0.052	15	+0.033	15	-0.016	2.2	1	●	●	●	●							
16	22	22	+0.052	16	+0.033	16	-0.016	2.2	1	●	●	●	●							
18	24	24	+0.052	18	+0.033	18	-0.016	2.2	1	●	●	●	●							
20	25	25	+0.052	20	+0.033	20	-0.02	2.2	1	●	●	●	●							
22	28	28	+0.052	22	+0.033	22	-0.02	2.2	1	●	●	●	●							
24	30	30	+0.052	24	+0.033	24	-0.02	2.2	1	●	●	●	●							
25	32	32	+0.052	25	+0.033	25	-0.02	2.2	1	●	●	●	●							
28	35	35	+0.062	28	+0.039	28	-0.02	2.2	1	●	●	●	●							
30	38	38	+0.062	30	+0.039	30	-0.02	2.2	1	●	●	●	●							
32	40	40	+0.062	32	+0.039	32	-0.025	2.2	1	●	●	●	●							
35	44	44	+0.062	35	+0.039	35	-0.025	2.2	1	●	●	●	●							
36	45	45	+0.062	36	+0.039	36	-0.025	2.2	1	●	●	●	●							
38	48	48	+0.062	38	+0.039	38	-0.025	2.2	1	●	●	●	●							
40	50	50	+0.062	40	+0.039	40	-0.025	2.6	1	●	●	●	●							
42	52	52	+0.074	42	+0.046	42	-0.025	2.6	1	●	●	●	●							
45	55	55	+0.074	45	+0.046	45	-0.025	2.6	1	●	●	●	●							
48	58	58	+0.074	48	+0.046	48	-0.025	2.6	1	●	●	●	●							
50	60	60	+0.074	50	+0.046	50	-0.025	2.6	1	●	●	●	●							
52	60	60	+0.074	52	+0.046	52	-0.03	2.6	1	●	●	●	●							
55	65	65	+0.074	55	+0.046	55	-0.03	2.6	1	●	●	●	●							
60	70	70	+0.074	60	+0.046	60	-0.03	2.6	1	●	●	●	●							
65	75	75	+0.074	65	+0.046	65	-0.03	2.6	1	●	●	●	●							
70	80	80	+0.074	70	+0.046	70	-0.03	3.2	1	●	●	●	●							
75	85	85	+0.074	75	+0.046	75	-0.03	3.2	1	●	●	●	●							
80	90	90	+0.087	80	+0.054	80	-0.03	3.2	1	●	●	●	●							
85	95	95	+0.087	85	+0.054	85	-0.036	3.2	1	●	●	●	●							
90	100	100	+0.087	90	+0.054	90	-0.036	3.2	1	●	●	●	●							
95	105	105	+0.087	95	+0.054	95	-0.036	3.2	1	●	●	●	●							
100	115	115	+0.087	100	+0.054	100	-0.036	3.2	1	●	●	●	●							
105	115	115	+0.087	105	+0.054	105	-0.036	3.2	1	●	●	●	●							

Notes: * Standard material: hardened spring steel - AISI6150, 50CrV4 (DIN1.8159), SUP 10, 50CrVA, CK67, 65 Mn etc.

* All sizes are in Metric " mm ".

* Special dimensions and tolerances are made to customer's request.

* Surface treatment is optional: Zinc plating / Phosphate coating / Tin plating.