


JOST Casting Bronze Flanged Guide Bushings 翻边导向铜套



Material Specifications 材料

材料: 青力黄铜
CuZn25Al8MnFe3

How To Order 订单方式


Code d L
● JOST 09 12

Unit(单位): mm

SinoBronze Standard No.	d	L	t	D	Tolerance 公差		D _i	d H7
					e7	k6		
JOST-9×12	9	12						
JOST-9×17	9	17					9	
JOST-9×22	9	22						
JOST-9×27	9	27						
JOST-9×36	9	36						
JOST-10×12	10	12	3	14			16	+0.015 0
JOST-10×17	10	17			-0.032 -0.050	+0.012 +0.001		
JOST-10×22	10	22					10	
JOST-10×27	10	27						
JOST-10×36	10	36						
JOST-12×17	12	17						
JOST-12×22	12	22					23	12
JOST-12×27	12	27		18				
JOST-12×36	12	36						
JOST-14×17	14	17						
JOST-14×22	14	22						
JOST-14×27	14	27					14	+0.018 0
JOST-14×36	14	36	6					
JOST-14×46	14	46						
JOST-14×56	14	56						
JOST-17×17	17	17		20	-0.040 -0.061	+0.015 +0.002	25	
JOST-17×22	17	22						
JOST-17×27	17	27						
JOST-17×36	17	36					15	
JOST-17×46	17	46						
JOST-17×56	17	56						

SinoBronze Standard No.	d	L	t	D	Tolerance 公差		D _i	d H7
					e7	k6		
JOST-16×17	16	17						
JOST-16×22	16	22						
JOST-16×27	16	27					27	16
JOST-16×36	16	36						
JOST-16×46	16	46						
JOST-16×56	16	56						+0.018 0
JOST-18×17	18	17						
JOST-18×22	18	22						
JOST-18×27	18	27						
JOST-18×36	18	36	6		-0.040 -0.061	+0.015 +0.002	18	
JOST-18×46	18	46						
JOST-18×56	18	56						
JOST-18×66	18	66						
JOST-20×17	20	17						
JOST-20×22	20	22						
JOST-20×27	20	27						
JOST-20×36	20	36					20	+0.021 0
JOST-20×46	20	46						
JOST-20×56	20	56						
JOST-20×66	20	66						

JOST Casting Bronze Flanged Guide Bushings 翻边导向铜套



Material Specifications 材料	How To Order 订货方式
材料: 黄铜 CuZn25AlMnFe3	Code d L ● JOST 22 22

Unit(单位): mm

SinoBronze Standard No.	d	L	t	D	Tolerance 公差		D1	d H7
					e7	k6		
JOST-22×22	22	22						
JOST-22×27	22	27						
JOST-22×36	22	36						
JOST-22×46	22	46						
JOST-22×56	22	56					22	
JOST-22×66	22	66						
JOST-22×76	22	76						
JOST-22×86	22	86						
JOST-24×17	24	17		30	-0.040 -0.061	+0.015 +0.002	35	
JOST-24×22	24	22						
JOST-24×27	24	27						
JOST-24×36	24	36					24	+0.021 0
JOST-24×46	24	46						
JOST-24×56	24	56						
JOST-24×66	24	66						
JOST-24×76	24	76						
JOST-24×86	24	86						
JOST-30×27	30	27	6					
JOST-30×36	30	36						
JOST-30×46	30	46						
JOST-30×56	30	56					30	
JOST-30×66	30	66						
JOST-30×76	30	76						
JOST-30×86	30	86						
JOST-30×96	30	96						
JOST-30×116	30	116		42	-0.050 -0.071	+0.018 +0.002	47	
JOST-32×27	32	27						
JOST-32×43	32	43						
JOST-32×46	32	46						
JOST-32×56	32	56						
JOST-32×66	32	66					32	+0.025 0
JOST-32×76	32	76						
JOST-32×86	32	86						
JOST-32×96	32	96						
JOST-32×116	32	116						

SinoBronze Standard No.	d	L	t	D	Tolerance 公差		D1	d H7
					e7	k6		
JOST-40×56	40	56						
JOST-40×66	40	66						
JOST-40×76	40	76						
JOST-40×86	40	86						
JOST-40×96	40	96					40	
JOST-40×116	40	116						
JOST-40×136	40	136						
JOST-40×156	40	156						
JOST-42×56	42	56		54			60	
JOST-42×66	42	66						
JOST-42×76	42	76						
JOST-42×86	42	86	10				42	+0.025 0
JOST-42×96	42	96			-0.060 -0.090	+0.021 +0.002		
JOST-42×116	42	116						
JOST-42×136	42	136						
JOST-42×156	42	156						
JOST-50×76	50	76						
JOST-50×86	50	86						
JOST-50×96	50	96						
JOST-50×116	50	116		66			72	50
JOST-50×136	50	136						
JOST-50×156	50	156						
JOST-50×196	50	196						
JOST-60×96	60	96						
JOST-60×116	60	116						
JOST-60×136	60	136		80			86	60
JOST-60×156	60	156						+0.030 0
JOST-60×196	60	196						