


JGLXS Casting Bronze Wear Plate 铜合金滑板



Dowel Hole Specs: 2:1:15

| | |
|---------|-------------------------------|
| W=20 | Dowel Dia: $\phi 6 \pm 0.015$ |
| W=25-30 | Dowel Dia: $\phi 8 \pm 0.015$ |



| Material Specifications 材料 | How To Order 订单方式 |
|----------------------------|--|
| 材料: 高力黄铜 CuZn25Al5MnFe3 | Code ● JGLXS W L T (23/28/32/42/53) |

Unit(单位): mm

| SinoBronze Standard No. | W | L | T | W1 | L1 | L2 | L3 | L4 | H | t | r |
|-------------------------|-----|------|-----|------|-----|-----|-----|----|---|-----|-----|
| JGLXS-20×60×T | 20 | 60 | 23 | 9 | 20 | 20 | 40 | 10 | 8 | 5.5 | 0.5 |
| JGLXS-20×80×T | | 80 | | | 50 | 20 | | | | | |
| JGLXS-20×100×T | | 100 | | | 70 | 40 | | | | | |
| JGLXS-20×120×T | | 120 | | | 45 | 15 | 60 | | | | |
| JGLXS-20×140×T | | 140 | | | 55 | 80 | | | | | |
| JGLXS-20×160×T | 160 | 65 | 100 | 17.5 | 30 | 10 | 7.5 | | | | |
| JGLXS-25×80×T | 80 | 45 | 20 | | | | | | | | |
| JGLXS-25×100×T | 100 | 65 | 40 | | | | | | | | |
| JGLXS-25×120×T | 120 | 42.5 | 60 | | | | | | | | |
| JGLXS-25×140×T | 140 | 52.5 | 80 | | | | | | | | |
| JGLXS-25×160×T | 160 | 62.5 | 100 | 11 | 20 | 40 | 15 | 11 | | | |
| JGLXS-25×180×T | 180 | 72.5 | 120 | | | | | | | | |
| JGLXS-25×200×T | 200 | 82.5 | 140 | | | | | | | | |
| JGLXS-30×100×T | 100 | 60 | 20 | | | | | | | | |
| JGLXS-30×120×T | 120 | 40 | 40 | | | | | | | | |
| JGLXS-30×140×T | 140 | 50 | 60 | 80 | 100 | 120 | | | | | |
| JGLXS-30×160×T | 160 | 60 | 80 | | | | | | | | |
| JGLXS-30×180×T | 180 | 70 | 100 | | | | | | | | |
| JGLXS-30×200×T | 200 | 80 | 120 | | | | | | | | |